INTERACTIVE LECTURE • AI & ROBOTICS 101

Reinforcement Learning:

Teaching Machines Through Trial, Error & Treats

An accessible, fun, and no-jargon guide to how modern robots learn to walk, manipulate objects, and master complex worlds without step-by-step human instructions.

Target Audience: Open to All | Prerequisites: Curiosity & Zero Math Anxiety

COURSE ROADMAP

[01] The 3 Pillars of AI

Where RL fits in Machine Learning

[02] AI in Robotics

Why moving in the real world is hard

[03] RL Fundamentals

Agents, Rewards & Exploration

[04] The RL Pipeline

Why Simulation & Sim-to-Real matter

[05] RL vs. Classical Control

When & why RL wins

How Do Machines Actually Learn? The 3 Paradigms

Imagine three different ways a student can study for a course: with flashcards, by sorting books, or by playing a game.

1. Supervised Learning

- **The Vibe:** Learning with a strict teacher & flashcards.
- **How it Works:** Every training example comes with a ground-truth label ('Cat' vs. 'Dog').
- **The Goal:** Predict the right label on new unseen data.
- **Fun Analogy:** Studying past exams where the answer key is printed at the back.
- **Real-World Use:** Spam filters, medical X-ray diagnosis, house price prediction.

2. Unsupervised Learning

- **The Vibe:** Detective work with zero labels.
- **How it Works:** The algorithm receives raw data and groups similar items together on its own.
- **The Goal:** Discover hidden structures, clusters, or anomalies.
- **Fun Analogy:** Dumping a giant box of LEGO bricks on the floor and sorting them by color/shape.
- **Real-World Use:** Netflix/Spotify recommendations, customer segmentation, fraud detection.

3. Reinforcement Learning

- **The Vibe:** Learning to ride a bike by falling and trying again!
- **How it Works:** No dataset! The agent interacts with an environment and gets rewards or penalties.
- **The Goal:** Maximize total cumulative reward over time.
- **Fun Analogy:** Training a dog with treats (+1) when it sits, and 'No!' (-1) when it chews your shoe.
- **Real-World Use:** Walking robots, AlphaGo, self-driving maneuvers, game AI.

Professor's Note: Key takeaway: Supervised Learning needs answers upfront; RL discovers answers through action and feedback.

Where Does Reinforcement Learning Fit?

Before zooming into RL, let's map out the family tree of Artificial Intelligence and Machine Learning.

1. Artificial Intelligence (AI)
The Broad Vision

Any system able to perform tasks that typically require human intelligence (chess programs, rule-based expert systems, smart assistants).

2. Machine Learning (ML)
Learning from Data Instead of Hardcoded Rules

Instead of programmers writing thousands of 'IF-THEN' rules, algorithms discover patterns directly from examples and experience.

3. Deep Learning (DL)
Brain-Inspired Multi-Layer Neural Networks

Uses giant artificial neural networks to process raw images, audio, and text (powers ChatGPT, facial recognition, and voice assistants).

4. Reinforcement Learning (RL) + Deep RL
Learning by Doing & Interacting

An active decision-maker (Agent) learns optimal actions through trial-and-error rewards inside a dynamic environment.

When Brains Meet Bodies: Why Robotics Needs AI

Why can a computer easily beat a World Chess Champion, yet struggle to fold a towel or walk on gravel?

MORAVEC'S PARADOX (1988)

"It is comparatively easy to make computers exhibit adult-level performance on intelligence tests or playing checkers, and difficult or impossible to give them the skills of a one-year-old when it comes to perception and mobility."

Why is the physical world so tough?

- Physics is messy (slippery floors, wind)
- Sensors are noisy and imperfect
- Every object has different weight & friction
- Split-second balance is required!

1. Agile Locomotion

- **Quadrupeds & Humanoids:** Walking over stairs, mud, snow, and rubble (e.g., ETH ANYmal, Boston Dynamics).
- **Dynamic Recovery:** Catching balance instantly when pushed or slipping on ice.

2. Dexterous Manipulation

- **Robotic Hands:** Solving a Rubik's Cube one-handed (OpenAI Dactyl) or rotating fragile fruit.
- **Deformable Objects:** Folding laundry, routing cables, or picking cluttered warehouse bins.

3. Autonomous Navigation

- **Agile Drones:** Champion-level FPV drone racing at 100 km/h (UZH Swift System in Nature 2023).
- **Self-Driving & Rovers:** Navigating crowded streets or rocky Martian craters autonomously.


4. Human-Robot Collaboration

- **Assistive Exoskeletons:** Adapting motor torque in real time to each user's walking gait.
- **Smart Cobots:** Working safely alongside humans on dynamic assembly lines.

PART 3 • REINFORCEMENT LEARNING FOCUS

How Reinforcement Learning Works: The Core Loop

At its heart, RL is a continuous conversation between an Agent (the learner) and its Environment (the world).



The 4 Building Blocks (MDP Vocabulary)

- **Agent (The Learner):** The brain making decisions—for example, the neural network inside a robot dog.
- **Environment (The World):** Everything outside the agent: gravity, floors, obstacles, and physics laws.
- **State (S_t):** What the agent observes right now (joint angles, camera pixels, IMU balance).
- **Action (A_t) & Reward (R_t):** The move the agent picks (motor torque) and the scalar score it receives back.

The Puppy Training Analogy

- **1. Observation (State):** Your puppy hears you say 'Sit!' and sees a treat in your hand.
- **2. Action:** The puppy experiments—maybe it barks, jumps, or sits down.
- **3. Reward:** Sitting yields a tasty biscuit (+10). Jumping yields no biscuit (0). Next time, sitting is much more likely!

Professor's Note: Remember: In RL, nobody tells the agent WHICH muscle to move—only HOW WELL it did via the reward score.

PART 3 • CORE RL CONCEPTS

The Art of the Reward: Careful What You Wish For!

RL agents are like literal genies: they don't do what you MEAN, they optimize the exact number you REWARD.

How Do We Score a Walking Robot?

- **Forward Velocity (+2.0):** Reward moving forward toward the target goal.
- **Staying Upright (+1.0):** Keep the torso level and above a minimum height.
- **Energy Penalty (-0.05):** Penalize violent, jerky motor torques so motion stays smooth and battery-friendly.
- **Collision / Fall (-100):** Heavy penalty if knees or head hit the ground.
- **Sparse vs. Dense Rewards:** Sparse = only +1 at the finish line (hard to learn!). Dense = continuous hot/cold hints every millisecond.

When RL Outsmarts the Professor ('Reward Hacking')

- **The Boat Racing Bug (OpenAI, 2016):** In the CoastRunners game, the AI found it could score more points by spinning in circles collecting regenerating turbo boosts on fire—never finishing the race!
- **The Tall Robot Cheat:** Asked to maximize hip height while jumping, a simulated robot learned to somersault upside-down on its stiff legs.
- **The Lazy Vacuum Cleaner:** Penalized for bumping into walls, a robot simply turned off its wheels and stood still forever (0 bumps = perfect score!).
- **The Lesson:** Designing a good Reward Function ('Reward Shaping') is one of the most critical engineering skills in RL.

Professor's Note: Reward Hypothesis (Sutton & Barto): All goals can be framed as maximizing expected cumulative scalar reward.

The Restaurant Dilemma: Exploration vs. Exploitation


It's Friday night! Do you order your favorite pizza again, or risk trying the mysterious new Thai place down the street?

Exploitation (Stick to What You Know)

- **The Strategy:** Pick the action that currently gives the highest known reward.
- **Pros & Cons:** Safe, reliable points right now—but you might get stuck in a mediocre local optimum and miss a 10x better strategy!

Exploration (Try Something Wild & New)

- **The Strategy:** Take random or uncertain actions to gather new information about the world.
- **Pros & Cons:** Might fail miserably in the short term, but it's the ONLY way to discover breakthrough skills!



Professor's Note: How engineers solve this: Start with 100% Exploration (curious baby) and slowly decay to Exploitation (skilled pro).

PART 4 • ARCHITECTURE & BUILDING BLOCKS

Inside the Engine: The 5-Stage RL Pipeline

A successful RL project is not just a clever algorithm—it is a complete engineering pipeline where every brick matters.

1. Environment & Task

- Define physics & rules
- Specify action space (torques/angles)
- Set episode reset conditions

2. State & Sensors

- Proprioception (joint encoders, IMU)
- Exteroception (cameras, LiDAR)
- Filter noise & normalize inputs

3. Reward Function

- Encode task goals clearly
- Add safety & smoothness terms
- Avoid reward hacking traps

4. Policy & RL Algorithm

- Neural network architecture
- Optimizer (PPO, SAC, DQN)
- Update weights from experience

5. Evaluation & Deploy

- Test on unseen perturbations
- Export fast onboard inference
- Deploy onto real robot hardware

The 'Weakest Link' Rule in Reinforcement Learning

- **Bad State Representation?:** The robot is flying blind—even the best algorithm (PPO/SAC) cannot learn if it lacks velocity or balance data.
- **Bad Reward or Physics?:** Garbage in, garbage out: a tiny bug in any single brick will cause the entire training pipeline to collapse.

Professor's Note: In industry, RL engineers spend 80% of their time tuning the Environment, State, and Reward—and only 20% on the algorithm!

PART 4 • IMPORTANCE OF SIMULATION

Why We Train in the Matrix: The Power of Simulation

Would you let a toddler learn to drive in a real Ferrari on a busy highway? Neither do roboticists!

SAFETY & COST

$0 Broken Parts

A real humanoid robot costs $100,000+. Falling 10,000 times on concrete destroys motors in minutes. In simulation, crashes are 100% free!

TIME COMPRESSION

10 Years in 1 Hour

GPU simulators (NVIDIA Isaac Lab, MuJoCo) run 4,096 virtual robots in parallel at 1,000x real-time speed.

INFINITE SCENARIOS

Instant World Reset

Spawn stairs, ice, wind gusts, or uneven rocks with one line of code—no need to build physical obstacle courses.

The Catch: The 'Sim-to-Real Gap'

- **What is it?:** Simulators are clean approximations; the real world has cable friction, motor delays, worn tires, and soft carpets.
- **The Risk:** A policy that walks perfectly in simulation might violently shake and collapse the moment it touches a real floor!

The Fix: Domain Randomization

- **How it Works:** During simulated training, we randomly vary gravity, floor friction, robot mass (±20%), sensor noise, and random pushes.
- **Why it Works:** If the robot can survive 1,000 crazy simulated physics worlds, the real world feels like just another variation! (Rudin et al., 2022)

Professor's Note: Real Benchmark: ETH Zurich & NVIDIA trained the ANYmal robot to walk in just 20 minutes on a single GPU using 4,000 parallel sims!

PART 5 • HEAD-TO-HEAD COMPARISON

Classical Control vs. Reinforcement Learning

How does RL compare to traditional robotics engineering (PID controllers, Trajectory Planning, Model Predictive Control)?

Comparison Dimension	Classical Control (PID, MPC, Rules)	Reinforcement Learning (Deep RL)
Core Philosophy	Sheet-Music Musician: Follows explicit physics equations written by human engineers.	Jazz Improviser: Learns flexible instincts from millions of trial-and-error episodes.
Physics Model Needed?	Strict Requirement: Needs accurate math equations of mass, inertia, and friction.	Model-Free Option: Can learn even when physics is too complex to write down (mud, cloth, water).
Sensor Inputs	Low-dimensional state (joint angles, clean coordinates). Struggles with raw pixels.	End-to-End Ready: Directly fuses raw camera images, LiDAR, and joint sensors into actions.
Online Computation	Heavy at runtime (MPC solves complex optimization math every millisecond).	Ultra-Fast at runtime (a trained neural network takes < 1 millisecond to output an action).
Weakness / Trade-off	Brittle when surprises happen outside the mathematical model.	Requires heavy upfront simulation training & careful reward engineering.

Professor's Note: Analogy: Classical control is a train on fixed tracks; RL is a mountain biker adapting to mud, roots, and rocks.

PART 5 • WHY CHOOSE RL?

4 Key Advantages of RL (And the Golden Hybrid Secret)

Why has Reinforcement Learning sparked a revolution in modern robotics and AI?

1. Masters Unmodeled Physics

• Excels when exact equations are impossible: walking on rubble, sand, snow, or handling deformable cloth.

2. Emergent Superhuman Skills


• Discovers creative moves no human coded (e.g., AlphaGo's Move 37, backflipping robots, drone racing).

3. Direct Vision-to-Action

• Maps raw camera/depth pixels straight to motor torques without brittle hand-crafted perception pipelines.

4. Lightning-Fast Execution

• Once trained, the policy is a compact neural network running in <1 ms on cheap onboard robot chips.



The Best of Both Worlds: Hybrid Control!

• **Modern Robotics Secret:** Combine a high-level RL Policy (for agile adaptation) with low-level Classical Safety Controllers (PD/MPC)!

Professor's Note: Rule of Thumb: Factory welding arm in a cage? Use Classical Control. Walking dog in a forest? Use RL!

Class Wrap-Up: What Should You Remember?

5 core lessons from today's lecture + a quick pop quiz to test your intuition!

The 5 Golden Takeaways

- **1. The 3 ML Paradigms:** Supervised learns from labels; Unsupervised finds patterns; RL learns through active trial-and-error.
- **2. Robotics Needs Adaptability:** Real-world physics is messy (Moravec's Paradox)—hardcoded rules break when environments change.
- **3. The RL Loop:** An Agent observes a State, takes an Action, and maximizes cumulative Reward by balancing Exploration & Exploitation.
- **4. Simulation is Essential:** We train thousands of virtual robots in parallel and use Domain Randomization to cross the Sim-to-Real gap.
- **5. RL vs. Classical Control:** Classical shines in structured factories; RL shines in complex, unstructured, dynamic worlds.

Pop Quiz! Test Your RL Intuition

- **Q1: You train a robot to pour coffee. It throws the mug across the room. What went wrong?:** Your Reward Function probably rewarded 'emptying the cup quickly' without penalizing spills!
- **Q2: Why can't we just train a real walking robot from scratch on the laboratory floor?:** It would take months of real time and destroy its hardware before learning to stand.
- **Q3: What happens if an RL agent uses 0% Exploration?:** It gets stuck repeating the first mediocre action that gave a tiny positive reward.
- **Verified References for Further Reading:** Sutton & Barto (2018) RL: An Introduction • Rudin et al. (2022) CoRL • Kaufmann et al. (2023) Nature.

Professor's Note: Thank you for your attention! Open the floor for student questions.